

## MOST COMMON AXLES BEARINGS & SEALS

---

For C-Clip Axles

B = Bearing

S = Seal

### For Shaft Size 1.399

B	5707	O.D. 2.255
S	8660-S	O.D. 2.296
	TRP-1563-TAV	Repair Bearing
B	513023	O.D. 2.445
S	4795-V	O.D. 2.750
	TRP-57509	Repair Bearing

### For Shaft Size 1.618

B	6408	O.D. 2.535
S	8835-S	O.D. 2.579
	TRP-1559-TV	Repair Bearing
B	513067	O.D. 2.807
S	4762-N	O.D. 2.849
	TRP-59047	Repair Bearing

### For Shaft Size 1.705

B	6410	O.D. 2.535
B	R1561TV	O.D. 2.997
S	710498	O.D. 2.579
S	710067	O.D. 3.039
S	3747	O.D. 3.090
S	710105	O.D. 3.090
	TGM 1561 R	Repair B for G.M
	TFO 1561 R	Repair B for Ford

### For Shaft Size 1.876

B	R1502EL	O.O. 2.782
S	414045	O.O. 2.786

## TAPERED AXLE BEARINGS

---

	Bearing #	Race #	I.D.	O.D.	Seal
Set 5	LM48548	LM48510	1.380	2.565	
Set 7	M201047	M201011	1.565	2.875	Inner 8695-S Outer 8704-S
Set 9	U298	U261 L	1.380	2.560	2146 & 712146 inner w/1.312 shaft - 473212 w/1.375 - 43214
Set 10	U399	U360L	1.565	2.875	9912 inner - 481837
Set 20	U399A	U365L	1.565	3.150	3195 incl.
Set 80	U497	U460L	1.775	3.150	35511

## MOST COMMON AXLES BEARINGS & SEALS

---

BALL BEARINGS	I.D.	Thicknesses	O.D.
RWF-34R 63-76 Dodge 7-1/4 Rear 9" Brake	1.340	.825	2.678
RW-207-CCR Mustang	1.380	.842	2.835
RW-507-CR 64-69 G.T.O. Firebird F-85	1.380	.658	2.749
RW-507-ER 55-56 Chevy Passenger	1.380	.885	2.835 w/ O-Ring
RW-607-NR 58-64 Chevy Passenger	1.380	1.00	3.00 w/ 2 O-Rings
RW-307R 57 Chevy Passenger	1.380	.902	3.00 w/ O-Ring Open Back
RWC-35YYR 71-80 Dodge 7-1/4 Rear 10" Brake	1.435	.700	2.875
63072RDC3-Mustang Axle to Large Ford End	1.380	.825	3.150
58503	1.532	.825	3.150 w/ O-Ring
58507	1.564	.825	3.150 w/ O-Ring Open Back
514003 Old #88128-R	1.535	.825	3.150
57803	1.565	.845	2.835
RW130-R	1.565	.902	3.544
58504-1	1.625		3.150
45-MIL	1.775	.825	3.150

We Now offer Steel Collars to replace crappy pot metal ones

For RW 207CCR	#207-Collar	Price \$8.75 each
For 514003	#514003-Collar	Price \$7.50 each

INNER AXLE SEALS	SHAFT SIZE	O.D.
51322	1.365	2.085
9569-S	1.365	2.264
9363-S	1.500	2.264
470059	1.500	2.378
9568	1.365	2.379
51098	1.500	2.506
8594-S	1.350	2.575